

Express Mail Certificate No. EV298592725US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR LETTERS PATENT

Applicants: YAN WANG
CHENG-KUNG CHENG

Title : FIXTURE FOR SPINES

6 Claims

4 Sheets of Drawings

William E. Pelton
Reg. No. 25,702
Donald S. Dowden
Reg. No. 20,701
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036
(212) 278-0400

1

2

3

4

7

8

1 to relocate the base (51) to secure the spine again.

2 To overcome the shortcomings, the present invention tends to provide an
3 improved fixture for a spine to mitigate the aforementioned problems.

4 SUMMARY OF THE INVENTION

5 The primary objective of the present invention is to provide an improved
6 fixture for a spine. The fixture has two engaging plates each having holes defined
7 therethrough and reinforced ribs extending between the two engaging plates.
8 With the structure of the fixture, the positioning effect to the damaged spine is
9 enhanced.

10 Another objective of the present invention is that each reinforced rib has
11 an extension extending into the spine such that the fixture is able to remain stably
12 seated onto the spine.

13 Other objects, advantages and novel features of the invention will
14 become more apparent from the following detailed description when taken in
15 conjunction with the accompanying drawings.

16 BRIEF DESCRIPTION OF THE DRAWINGS

17 Fig. 1 is an exploded perspective view of the fixture of the present
18 invention;

19 Fig. 2 is an exploded perspective view of another embodiment of the
20 fixture of the present invention;

21 Fig. 3 is a schematic view showing the application of the fixture of the
22 present invention; and

23 Fig. 4 is a top plan view of a conventional spine fixture.

24 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

1 With reference to Fig. 1, the fixture (10) in accordance with the present
2 invention has a first engaging plate (11), a second engaging plate (12) and
3 reinforcing ribs (13) interconnecting the two engaging plates (11,12).

4 The first engaging plate (11) has at least two first holes (111) (two are
5 shown in this embodiment). The second engaging plate (12) has at least two
6 second holes (121) (two are shown in this embodiment). Each second hole (121)
7 has a configuration the same as a numeral eight (8). Each reinforcing rib (13) is
8 sandwiched between the first engaging plate (11) and the second engaging plate
9 (12) and has an extension (131) integrally formed with the reinforcing rib (13).

10 With reference to Fig. 2, it is noted that there are three reinforcing ribs
11 (13) formed between the first engaging plate (11) and the second engaging plate
12 (12). Screws (20) are applied to correspond to the first holes (111) and the second
13 holes (121) in both embodiments.

14 With reference to Fig. 3, when the fixture of the present invention is in
15 application, the operator is able to use the screws (20) to extend through at least
16 one of the first holes (111) and both of the two second holes (121) depending on
17 the location of the damage of the spine (30). A gap (132) defined between the
18 two adjacent reinforcing ribs (13) is provided to allow the technician to have
19 access to the cartilage in the spine such that the technician is able to remove the
20 cartilage partially and apply medical powder to treat the damaged spine. It may
21 be understood that there may be provided with a through hole (not shown) in a
22 bottom defining the gap (132) so that the medical powder applied to the damaged
23 spine can engage with the spine directly. Due to the shape of the second holes
24 (121), the operator not only can adapt to the location of the damage of the spine,

1 the technician can also secure the bolts (20) relative to the second engaging plate
2 (12). Therefore, even after a long period of time of using the fixture of the
3 present invention on a damaged spine, concern about the fixture possibly
4 becoming loose is obviated. Furthermore, the extension (131) of each of the
5 reinforcing ribs (13) is able to be seated in a groove defined in the spine to
6 enhance the engagement of the fixture to the spine (30).

7 It is to be understood, however, that even though numerous
8 characteristics and advantages of the present invention have been set forth in the
9 foregoing description, together with details of the structure and function of the
10 invention, the disclosure is illustrative only, and changes may be made in detail,
11 especially in matters of shape, size, and arrangement of parts within the
12 principles of the invention to the full extent indicated by the broad general
13 meaning of the terms in which the appended claims are expressed.